D2002 / D2002R

2-Channel Power Amplifier for High-Quality Portable Sound Systems



☑ Touring
☐ Installation

2 CH

- Small-scale portable systems
- Compact full-range loudspeakers
- Delay lines
- Stage monitors
- Live and dance clubs
- Corporate events (speech, background music, AV presentations)

2-channel mode			mono-bridged mode	
2 Ω	4 Ω	8 Ω	4 Ω	8 Ω
2 x 1,000 W	2 x 600 W	2 x 350 W	1 x 2,000 W	1 x 1,200 W

EIAJ Test Standard, 1 kHz, 1% THD

The **D2002** is a solid workhorse in any environment: on the road where things get tough or permanently installed, it provides its service dependably over many years.

Due to unique technologies inside such as the switch mode power supply with PFC and the distinct Class D output stage, the **D2002** is highly efficient, resulting in lower power consumption. This means lower operational costs and decreased energy draw from the environment, in line with Green Audio Power® technology – typical Powersoft.

Performance is key, and the **D Series** is at the forefront of uncolored sound reproduction – simply put, the **D2002** sounds great.

For where required or demanded, the **D20042** version comes factory-equipped with a communication port, allowing remote control and monitoring on the same network as all other Powersoft amplifiers via the same Armonía Pro Audio Suite™ software.

Both the **D2002** and the **D2002R** come with 4 years warranty and, like all Powersoft products, are entirely designed and made in Italy.

✓ **Legendary Powersoft efficiency:**
- Unequaled Class D design with fixed switching frequency
- Universal switch mode power supply with PFC (Power Factor Correction)
- Space and weight saving: only one rack space (1 RU) and 9.5 kg / 20.9 lbs
- Green Audio Power®: more amplifier output power from the AC mains power distribution due to >80% efficiency

✓ **Outstanding performance and sonic quality by design**, including amp clip limiters and patented ripple cancellation network

✓ **Practically versatile:**
- Mono-bridgeable channel pairs
- Linking analog signal inputs per switch
- Built-in filter network, internally selectable per channel: high/low/band pass, 12 dB/oct, 65/100/130 Hz
- Built-in gate, internally selectable per channel: off/-50 dBu
- AC inrush current limiting; channel output voltage limiting
- Recessed stepped level attenuators; front LED's for all relevant information

✓ **Fully protected circuit design:**
- AC protection: shuts down power supply when AC mains voltage is outside operating range
- Clip limiter: prevents severely clipped waveforms from reaching loudspeakers, while still maintaining full peak power output
- DC protection: protects against infrasonic signal at the outputs
- VHF protections: protects the loudspeakers against destructive non-audible, non-musical high frequency signals
- Short circuit protection: protects the amplifier from short circuit or similar events on the outputs; with automatic protection reset
- Thermal protection: mutes outputs once output devices reach 75 °C / 167 °F; automatic unmute once temperature is down to 65 °C / 149 °F
- Long-term RMS protection: preventing loudspeaker damage from continuous non-audio signals by reducing output power


✓ Front-to-rear airflow cooling with variable-speed fan, temperature controlled

✓ Full four years warranty

✓ Options & accessories:
- "R" model – including comm port for remote monitoring per PC:
  - On-board RS485 serial communication port on rear panel, for amplifier control and monitoring via Armonía Pro Audio Suite™ software
  - Digitally controlled amplifier providing feedback of status information
- Armonía Pro Audio Suite, free at www.armoniasuite.com
- Power Control Hub, RS485 distribution and remote Power-on unit for up to eight amplifiers, 19"/1 RU

D2002 / D2002R

2-Channel Power Amplifier for High-Quality Portable Sound Systems



Specifications

General						
	Number of channels	2				
	Output power	2-channel mode			mono-bridged mode	
	EIAJ Test Standard, 1 kHz, 1% THD	2 Ω	4 Ω	8 Ω	4 Ω	8 Ω
		2 x 1,000 W	2 x 600 W	2 x 350 W	1 x 2,000 W	1 x 1,200 W
	Max output voltage	74 V_{peak}				
AC Mains Power						
	Power supply	Universal, regulated switch mode with PFC (Power Factor Correction)				
	Operating voltage	100 V - 240 V ± 10%, 50 Hz - 60 Hz				
	Power factor cos (φ)	>0.95 @ >200 W				
	Consumption / current draw		@ 230 V	@ 115 V		
	Idle	87 VA	0.38 A	0.76 A		
	1/8 of max output power @ 4 Ω [1]	188 VA	1.2 A	2.4 A		
	1/4 of max output power @ 4 Ω [1]	375 VA	2.0 A	4.0 A		
Thermal						
	Environmental operating temperature	0° - 45° C / 32° - 113° F				
	Thermal dissipation	Fan, continuously variable speed, temperature controlled, front to rear airflow				
	Idle	60 kcal/hr	239 BTU/hr			
	1/8 of max output power @ 4 Ω [1]	93 kcal/hr	367 BTU/hr			
	1/4 of max output power @ 4 Ω [1]	125 kcal/hr	495 BTU/hr			
Audio						
	Gain	32 dB				
	Input sensitivity @ 8 Ω	1.32 V / 4.63 dBu				
	Input filters	Internally selectable per channel: high/low/band pass, 12 dB/oct, off/65/100/130 Hz				
	Gate	Internally selectable per channel: off/-50 dBu				
	Input impedance	10 kΩ				
	Frequency response	5 Hz - 30 kHz (+/-3 dB)				
	THD+N / SMPTE IMD DIM100 IMD	typ. <0.1% (<0.5% @ >0.1 W) typ. <0.01% (<0.02% @ >0.1 W)				
	S/N ratio (amplifier section)	>105 dB(A)				
	Crosstalk separation	>70 dB @ 1 kHz				
	Slew rate	40 V/µs @ 8 Ω, input filter bypassed				
	Damping factor	>600 @ 100 Hz				
Front Panel						
	Indicators	3 LED's per channel for output level: 3 x green, 1 x yellow, 1 x red 2 status LED's per channel: green for signal present (-66 dBV), red for protection 2 status LED's: green for amplifier ready, yellow for thermal protection				
	Controls	1 stepped level attenuator pot per channel Mains power on/off switch				
Rear Panel						
	Audio signal input connectors	2 x Combo XLR female/1/4" jack, electronically balanced				
	Loudspeaker output connectors	2 x Speakon® NL4MD				
	Controls	Link switch, linking inputs 1 and 2				
	AC mains	IEC C13 16 A (AC mains cord with 3-pin plug 15A for U.S., IEC 'Schuko' 16A for else)				
	Remote control interface (optional "R" version)	RS485: 1 x RJ45 with 2 x rotary address switches				
Construction						
	Dimensions	W 483 mm / 19", H 44.45 mm / 1.75" / 1 RU, D 455 mm / 17.9"				
	Weight	8.5 kg / 18.7 lbs				
	Side & rear reinforcement, front panel	5 mm steel				
	Top & bottom lid, rear panel	1 mm steel				

1) With pink noise.

Data is subject to change without notice.
© 2012 Powersoft • All rights reserved.

SONOSELF
LOCATION AUDIOVISUEL par VIDEOSON
8 rue du Château d'Eau · 78790 Courgent
01 39 24 84 84 · contact@sonoself.fr
sonoself.fr
Ce matériel en location sur sonoself.fr